

Remarks/Arguments

I have responded to the examiners request to remove the informalities and rewritten my claims to conform to patent office requirements.

I have narrowed my claims to reflect what I believe represents an advance over the prior Patented state of the art. I claim a single heat transfer loop between solar collector and hot water tank filled completely with an automotive type antifreeze/water mixture, where air is eliminated by the normal thermal expansion of the heat transfer fluid in the day and its subsequent cool down at night, excluding the air is important, because air speeds up corrosion. The fluid loop is also capable of safely dissipating the heat collected by the solar collector to the outside air by allowing the fluid to boil under pressure, if fluid circulation stops. The fluid loop, consisting of the solar collector: a screw into your existing hot water tank heat exchanger; a circulation pump; a pressurized radiator and or air vents to regulate the pressure and temperature in the system; a means to exclude air from the pressurized loop and tubing to connect the pump, solar collector, pressure/temperature regulator and heat exchanger together. The examiner has convinced me that the umbilical I previously claimed was anticipated by prior art. I believe the air exclusion system, pressurized liquid to air radiator and pressure activated dampers have not been anticipated nor claimed by the prior art.

The solar system in Claim 1:

The heat transfer loop uses a self pressurizing water based antifreeze fluid at about 16 PSIG pressure, with a means to control the pressure at 16 PSIG, a means to catch the fluid overflow, and a means to return fluid without air to the antifreeze fluid loop, keeping the antifreeze loop full of fluid, while excluding air. The heat transfer loop uses a radiator between the solar collector and the pressure relief/fluid vacuum recovery valve to dissipate heat from the collector when the fluid flow is stopped. This solar collector heat makes pressurized steam at 265°F, this steam proceeds to the pressurized radiator which is at the highest point in the system and is condensed to fluid by giving up heat to the outside air. The condensed fluid stays inside the antifreeze fluid loop. The radiator is part of the closed fluid loop system and is not open to the atmosphere, so no oxygen is present to dissolve in the antifreeze fluid and cause corrosion.

The fluid loop uses an antifreeze fluid which is maintained full of fluid and excludes corrosion causing air. Fluid thermal expansion self pressurizes the loop to the pressure cap level. The boiling of the pressurized fluid in the solar collector upon circulation stoppage activates a means of over-temperature protection, while keeping the collector full of fluid with metal temperature no greater than 265 degrees Fahrenheit. The collector is protected from over-temperature by either steam condensing in the pressurized radiator giving up its heat to the outside air, and or steam pressure activating a set of dampers to allow outside air to cool the collector directly.

In Embree (US 4269167) the system is pressurized with air to 4 psi, with the heat transfer fluid and several cubic feet of air, so the air can displace the fluid in the solar collector so the fluid can drain back out of the collector and piping. In Embree, fluid flow stoppage will allow air into the collector, as the fluid drains out of the collector. Embree does not have a provision to prevent the solar collector from overheating if fluid flow stops. Collector metal temperatures in excess of 500 degrees Fahrenheit will result as will deposition of scale, both conditions will enhance corrosion and lead to collector tube blockage. In addition the air pressurized in the system will dissolve in the water and accelerate system piping corrosion. Incomplete drain down of the system can cause pipes to burst from freezing. Embree does not anticipate a system full of fluid, without air, which keeps the solar collector from overheating when the pump is shut off.

Scharfman (US 4043317) does disclose an over-temperature protection system using dampers to cool the solar collector if circulation stops. He does anticipate dampers, but not their activation by system pressure, which is the basis for my claims 1 and 3. Scharfman does not anticipate a pressurized radiator, which can dissipate solar collector excess heat to the surrounding air, without the use of dampers, as I recite in claim 2.

Sigworth, Jr. (US 4413615) recites a solar system that uses heat transfer oil between the solar collector and storage tank. His oil does not boil or freeze between -40 and 500 degrees Fahrenheit. The oil has a low vapor pressure, so he does not need a pressurized system. He uses thermal buoyancy forces to move the fluid. He uses an expansion tank and simple backflow check valve. If his valve sticks closed and fluid circulation stops, the oil can reach 500 degrees Fahrenheit and break down in the collector. He has no phase change from water to steam to help protect his system from over-temperature. Oil does not undergo the phase change I recite, water to steam, to limit the collector temperature, and generate the pressure needed to operate pressurized radiator or the pressurized dampers to keep the collector cool. He does not anticipate a water based antifreeze fluid as I claim.

Zinn (US 4413615) recites the umbilical that I had claimed as claim 4. I have canceled this claim, since it is already patented.

I believe that the system I claim is not anticipated by the patents cited above when taken together. Someone skilled in the art would not extend the above patents to a system which protects the solar collector from overheating upon circulation stoppage by the actions of the water to steam phase change at 16 psi pressure and 265 degrees Fahrenheit. The steam either condenses in the pressurized radiator dissipating the heat, or actuates dampers which allow air to cool the collector. The patents cited above, do not have a means to allow liquid and gas to escape through a pressure relief valve and only liquid to be returned to the system via a vacuum relief valve to keep the system full of fluid and exclude air.

The Boiling Activated Pressurized Radiator Heat dissipation system Claim 2:

The solar collector will begin boiling at 265°F if the fluid circulation stops, since the pressure relief Valve is set at 16 PSIG. The steam from the solar collector makes its way toward the pressure relief valve through a liquid/steam separator. Before the steam gets to the pressure relief valve it encounters the pressurized liquid to air radiator, where it condenses from steam back into liquid. Most of the steam never gets to the pressure relief valve, where it could exit the pressurized fluid loop and be injected into the bottom of the overflow recovery reservoir, where it would be condensed into liquid by the liquid in the reservoir. Any steam left in the solar collector when the sun goes down will condense causing a vacuum in the solar collector fluid loop. This causes the vacuum relief valve to open letting fluid from the bottom of the overflow reservoir reenter the closed fluid loop. Air over the fluid in the reservoir can not enter the closed fluid loop, since the entrance is always below water level.

Prior art Goto (JP 59-93149 A) recites that the solar collector with water based antifreeze fluid will begin boiling at 220°F if the fluid circulation stops, since the system is open to the atmosphere. The steam from the solar collector makes its way toward the atmosphere. Before the steam gets to the atmosphere it encounters the liquid to air radiator, where it condenses from steam back into liquid. The condensed steam moves by gravity back into the fluid loop through a liquid/steam separator. This system does not have a means to keep air from mixing with the steam and keeping air from dissolving in the heat transfer fluid. The dissolved air will enhance system corrosion. Goto does not recite a reservoir, to keep the system full of fluid, since he is open to the atmosphere evaporation losses from the system will occur and fluid will need to be added over time. The Goto system looks very similar, but is unpressurized, so even a 50/50 water/antifreeze mixture would boil at 220°F, which is much lower than the 265 °F I claim using 16 PSIG pressure. Goto et al. recites a radiator to control boiling, but has no pressure relief/vacuum refill valve and uses gravity to allow the liquid to go back into the fluid loop using a steam/liquid separator.

The pressure activated solar collector over-temperature protection Claim 3:

Uses the pressure generated by the solar collector boiling at about 265°F to activate airflow dampers in solar collector. This system uses the steam pressure to operate a piston to open the dampers on the solar collector. When the collector cools, the steam generation stops and the dampers close.

Scharfman (US 4043317) does disclose an over-temperature protection system using dampers to cool the solar collector if circulation stops. Scharfman uses temperature activation devices, expanding wax, bimetals, electronic temperature sensors controlling actuators; no one recites using system pressure. Scharfman does anticipate dampers, but not their activation by system pressure, which is key to my claims 1 and 3. Scharfman

Appl. No. 10/085,175
Amdt. Dated June 5, 2004
Reply to Office Action March 05, 2004

does not anticipate a pressurized radiator, which can dissipated solar collector excess heat to the surrounding air, without the use of dampers, as I recite in claim 2.

Applicant respectfully requests that a timely Notice of Allowance be issued in this case.

Respectfully Submitted,

A handwritten signature in black ink that reads "Barry L. Butler". The signature is written in a cursive style with a large, stylized "B" and "L".

Dr. Barry L. Butler

Tel: 858-259-8864

United States Patent Application

Docket Number: 10/085,175

Dr. Barry Lynn Butler

980 Santa Estella

Solana Beach, California 92075

SS# 156-34-3255

Date of Filing: 2/27/2002

Federal R&D: None

Assignment: None

Related Applications: Internal

Water Tank Solar Heat Exchanger –
10/085,174

Deleted:

SOLAR HEAT TRANSFER SYSTEM (HTPL), High Temperature Pressurized Loop

BACKGROUND OF INVENTION

This invention pertains to collection and delivery of heat from a roof or ground mounted solar collector panel to a hot water storage tank via the use of a liquid filled pressurized fluid loop and a single pump. The pressurized loop system utilizes a water/antifreeze mixture or other suitable fluid, excludes corrosion-causing air and is circulated via a pump. In addition, the system is protected from over-temperature and over-pressure via a pressurized radiator or pressure activated dampers on the solar collector if the circulating pump power is lost or the controller turns the pump off. The high temperature fluid heat transfer loop allows for a smaller heat transfer area and hence more compact, hot water tank heat exchanger which adapts to existing hot water tanks. The system includes a small diameter, i.e. 2 inch, flexible insulated umbilical containing both electrical and approximately 1/4 inch outside diameter fluid tubing, to go between the hot water tank and the solar collector for ease of installation. The saving in both

Deleted:

Deleted: fails

Deleted: and a

Deleted: approximately

Deleted: Inch

Deleted: diameter

Deleted: fluid tubing connections,

Deleted: to and from

Deleted: to

complexity and materials for heat exchangers, piping, insulation, and the self-protection from freezing, overheating and over-pressure, makes this solar collector system unique.

Deleted: ,

Deleted: make

Deleted: collector

PRIOR ART

Most common solar collector systems are unpressurized and use a heat exchanger external to the water tank to exchange heat from the unpressurized solar loop to the city water pressure in the hot water tank. Unpressurized solar collector heat transfer loops are limited to the boiling point of water/antifreeze mixtures, typically 50/50, at atmospheric pressure which is approximately 220 degrees Fahrenheit. A water antifreeze mixture of approximately 50/50, pressurized to sixteen PSI (or approximately two atmospheres) in the solar collector loop will not boil until 265 degrees Fahrenheit. The higher operating temperature in the solar collector loop allows for smaller surface area internal hot water tank heat exchangers to be utilized, which do not disturb the normal tank stratification. Using an internal tank heat exchanger also eliminates the pump from the hot water tank through the external heat exchanger. Circulating water from the hot water tank, through the external heat exchanger disturbs the stratification of the hot water tank, hot on top and cooler on the bottom. It is important not to disturb the normal tank stratification, because it decreases the normal gas or electric water heater efficiency.

Deleted: -

Deleted: -

Deleted: -

Deleted: collector

Deleted:

Deleted: of

Deleted: fourteen

Deleted: ,

Deleted: collector

Deleted: collector

Deleted: efficient

Deleted: , which

Deleted: Internal

Deleted:

Deleted: would circulate water

Deleted: The

Deleted: normal

Deleted: , is disturbed by circulating water from the hot water storage tank, through the external heat exchanger

Deleted: ,

Deleted: C

Deleted: line

Deleted: this

Some solar collectors use city water pressure and flow the potable city water through the collector to heat it. If the solar collector is in a freezing environment then the potable water must be drained to prevent freeze damage to the solar collectors. There are two methods of freeze protection for potable water in solar collector systems. The first method is to drain all of the water out of the solar collector during freezing conditions and second method is to supply heated water to the solar collector to keep the solar collector from freezing. The first method of freeze protection by draining the solar collector system includes two approaches, drain down and drain back. Drain down

systems use a special "spool" valve to shut off the solar collector supply water and send the collector water down the drain. The drain back systems have a separate solar collector fluid sump tank near or included in the hot water tank. The heat transfer fluid drains from the solar collector into this sump tank inside the home to prevent freezing when the pump shuts off. The second method of system freeze protection heats the solar collector water using electrical resistance heating elements external or internal, as integrated solar collector storage systems do, or provide heat by bleeding a small amount of hot water from the hot water tank through the solar collector continuously to keep it from freezing. Both of these types of heat adding systems must sense freezing conditions and take appropriate actions. Failure to detect freezing or take action results in burst pipes. Hence drain down or drain back systems are not freeze proof, unlike the antifreeze/water filled systems, which are freeze proof.

Main advantages of the invention using the pressurized antifreeze/water fluid loop are : 1) pressurized water/antifreeze heat transfer loop is freeze proof and allows the solar collector to operate up to 265 degrees Fahrenheit; 2) the high temperature heat transfer loop allows heat to be transferred with very low fluid flow rates, minimizing pumping power and allowing small diameter tubes to take fluid to and from the solar collector and water tank heat exchanger; 3) internal heat exchanger adapts to existing tanks with minimum re-plumbing and without tank removal or draining; 4) the pressurized fluid radiator, steam pressure activated dampers, pressure relief, vacuum relief, overflow recovery system limits both solar collector temperature and fluid pressure while keeping the system full of fluid and eliminating air from the system to minimize corrosion; 5) double wall heat exchanger safely separates toxic heat transfer fluids from potable water; 6) this solar system has only one pump and is easier to install and maintain than two tank, two pump systems; and 7) The solar system internal hot water tank heat exchanger maintains normal tank stratification, maintaining the backup electrical or gas system efficiency.

Deleted: These systems are called integrated collector storage, roof mounted systems. The city potable water is subject to freezing and must be heated electrically at night to keep the collector from freezing during cold weather. Other systems, which circulate potable through the collectors when they're illuminated by the sun, must drain this water out at night during freezing weather.

Deleted: Pressurized

Deleted: Allows

Deleted:

Deleted: s

Deleted: Pressurized

Deleted:

Deleted: Internal

Deleted: 2

Deleted: Heat exchanger is efficient

Deleted: 3

Deleted: Double

Deleted: 4

Deleted: This

Deleted: costs less

Deleted: 5

Deleted: Solar

Deleted:

SUMMARY OF INVENTION

In summary, the present invention is a pressurized fluid loop, where heat is collected in a solar panel illuminated by the sun, heats a solution of water based antifreeze or other suitable liquid. The fluid is pumped at low flow rate to a hot water tank where it gives up the heat via an internal heat exchanger, then returns to the solar collector at a low flow rate in small tubing. The fluid loop is pressurized and operates above the normal boiling point of water, 212 Fahrenheit, and automatically eliminates air from the heat transfer fluid loop. The fluid loop also has built in over-temperature and over-pressure protection, so if the fluid circulation pump stops, the solar collector will not get too hot and damage itself, because the steam generated in the solar collector is either condensed in the pressurized steam/liquid to air heat exchanger and or opens the pressure actuated dampers on the solar collector to let outside air cool the solar collector.

Deleted: Pressurized

Deleted: .

Deleted: t

Deleted: built in

Deleted: that

Deleted: system

Deleted: itself

Deleted: .

The primary objective of the present invention is to reduce the amount of material and complexity needed to collect and transport solar heat, while automatically protecting the fluid loop from freezing using antifreeze and over-temperature by pressurized boiling. This is accomplished by increasing the temperature in the fluid loop which allows more heat to be stored in each unit volume of fluid in the solar collector heat transfer loop. Hence a smaller volume of fluid at a lower flow rate, is needed to deliver the heat from the solar collector to the hot water tank. The higher fluid temperature difference between the hot water tank and the fluid loop decreases the surface area required for heat exchange inside of the hot water tank. The higher pressure fluid loop uses steam created in the solar collector when fluid circulation stops to protect the solar collector and fluid loop from over-temperature by dissipating the heat safely in the pressurized steam/fluid to outside air radiator and or via pressure actuated dampers on the solar collector to allow outside air to flow over the solar collector. These steam/pressure based means allow the solar heat to be dissipated safely and make the system self protecting in case of loss of fluid flow.

Deleted: u

Deleted: , which decreases the area of the hot water tank to fluid loop heat exchanger surface

Deleted: The higher fluid temperature difference, between the hot water tank and the solar collector allow more heat to be stored in each unit volume of fluid in the solar collector heat transfer loop.

Deleted: .

Deleted: .

Deleted: temperature in the collector will lower the collector's efficiency, since it is losing heat to the outside air. This loss is a small price to pay for a system using significantly less material.

Another objective is to reduce the time and complexity of retrofitting solar energy to existing homes. The present invention uses flexible small diameter tubing to carry the low fluid flow volume in the system. The small diameter of the fluid carrying tubes, approximately $\frac{1}{4}$ inch outside diameter, also allows the tubes to be thermally insulated and still be less than 2 inches in diameter when bundled together. By adding an electrical wire bundle to the insulated fluid carrying tubes and placing them in a protective covering, an umbilical is created, which carries all fluids and electrical signals from the hot water tank to the solar collector. This "plug and play" umbilical allows do-it-yourselfers and professionals to install the system more quickly. These fluid carrying tubes can be installed in existing buildings, because they are flexible and can be fed into and through attics, walls or placed on the outside of buildings.

Formatted: Font: Not Italic

Deleted: ,

Deleted: since it

Deleted: inc

Deleted: them

Deleted: wrapping

Deleted: with

Deleted:

Deleted: cord

Deleted: for

Deleted: or

Deleted: and

Deleted: , without being unsightly

Additional objectives, advantages and novel features of the invention will be set forth in part in the description which follows and in part will become apparent to those skilled in the art upon examination of the following. Others may be learned by practice of the invention. The objectives and advantages of the invention may be realized and attained by means of the instrumentalities and combinations particularly pointed out in the appended claims.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of the pressurized loop solar collector system, including the fluid loop, the solar collector, the hot water tank heat exchanger, the fluid pump, pressurized fluid/steam to outside air radiator, pressurization valve, vacuum relief valve, overflow/recovery system, air elimination system and controller. The boiling activated pressurized radiator over-temperature and pressure activated over-temperature systems are shown schematically.

Deleted: and

Deleted: the

Deleted: over-pressure

FIG. 2 is a view of the boiling activated fluid/steam to air pressurized radiator solar collector temperature limiting system and fluid pressurization, vacuum relief, overflow/recovery system,

Deleted: over-pressure

Deleted: its associated

Deleted: , with the external fluid recovery system

FIG. 3 is a pressure activated solar collector over-temperature control system, which upon fluid loop boiling opens dampers in the solar collector to allow outside air-cooling of the solar collector,

Deleted: which

Deleted: let heat out

Deleted: , when the fluid in the loop boils and raises the loop pressure

FIG. 4 shows the details of a gas/liquid separator for the boiling activated fluid/steam to outside air radiator solar collector over-temperature system, which upon boiling forces steam and fluid from the main fluid loop into a liquid to air heat exchanger, a radiator, where it is cooled,

Deleted: is a

Deleted: control

Deleted:

Deleted: , to

Deleted: let heat out of the fluid loop, when the fluid in the loop boils

FIG. 5 is a plot of air valve position versus pressure in the solar collector fluid loop.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The invention (FIG. 1) consists of a pressurized heat transfer loop (1, 14 & 17), which operates well above the boiling point of water at one atmosphere of pressure, 212 degrees Fahrenheit. The heat transfer fluid (13) is heated in the solar collector tube (1) by the sun. The solar collector (2) can be single or double-glazed. The heated fluid then exits the solar collector in tube (1) and comes to a three-way connection. Path one (7) goes to the pressure actuator (6), which can move actuator arm (5) to actuate air dampers with motion (4). Path one may not be needed if the path two pressurized fluid/steam to air radiator is sufficient to prevent overheating. Path two goes through a pressurized radiator (8) with fins (9) to a pressure relief valve (10) which includes a vacuum recovery valve to let expelled heat exchanger fluid (13) back into the system from the fluid overflow/recovery reservoir (12), while excluding air. Path three (14) is the fluid tubing

Deleted: (FIG. 1)

Deleted: water

Deleted: ,

Deleted: ,

Deleted: in the

Deleted: ,

Deleted: double glazed

Deleted: , solar collector (1)

leading to the hot water tank (22) heat exchanger (16). The insertable, internal heat exchanger screws into the tank through a tank port (24) and provides water tank fluid (30) ingress or egress via a side port (26). The inside of the outer heat exchanger wall (16) is in physical contact with the outside of tubes (14 & 17). Physical contact means that over a significant area or approximately 50% of the surfaces, the interfaces are compressed together mechanically so heat can cross the interface, but leaking liquid from either side will move along the interface. Tube (14) turns around in the bottom of the heat exchanger and becomes tube (17) exiting the heat exchanger. Tubes (14 & 17) are much hotter than the water in the hot water tank (30) and are in physical contact with wall (16) so the heat is transferred from heat transfer fluid (13) through the first wall (14 or 17) then through the mechanical interface to the second wall (16) then into the water (30). Once tube (17) leaves the heat exchanger it returns to the pump (20) inlet. Tube (17) then returns to the solar collector tube (1) for heating of fluid (13).

To transport the pressurized fluid and the heat it contains from the solar collector to the hot water heater a flexible insulated umbilical is used (15). The umbilical consists of thermally insulated fluid connections (14 & 17) from the solar collector (1 & 2) to the hot water tank, rubber closed-cell thermal insulation (32), the low voltage electrical connections and a weather resistant covering of polymer pipe (31), the two small diameter tubes (14 & 17) containing the solar collector heated fluid (13). This allows the two-tube bundle to be flexible and insulated with about ¾ inch thick insulating jacket (32) and still be less than 2 inches in diameter. The small diameter copper tubes are connected together with standard tubing unions, angles and T-connectors of about 1/4 inch size.

The system has two possible configurations for activating the heat transfer fluid pump (20). The first is a conventional control system run from household 115VAC power. This control system has a control box (52), which plugs into the wall outlet and has two sensors. The collector has a temperature sensor using low voltage (50) where the electrical wires are part of the umbilical, to tell the controller, which turns on the pump, when the collector temperature exceeds the hot water tank temperature, measured by

Deleted: 12

Deleted: 11

Deleted: three

Deleted: 8

Deleted: who's

sensor (16) at the bottom of the hot water tank. There may also a sensor in the top of the tank (64), which tells the controller the tank is getting too hot, i.e. no one home to use hot water, then the controller will shut off the pump. This would now cause the pressure damper or side channel heat exchanger to protect the collector from excessive boiling, which would block the collector tubes with scale over time.

Deleted: 10

Deleted: is

Deleted: 9

Deleted: will

Deleted: in

The second pumping system is based on using a photovoltaic array (60), which provides 12 Volt power when the sun is shining. This power is carried down to the pump on the umbilical connector wire. The pump is a DC powered pump, which is capable of low flow at modest pressures. A control box may not be necessary. When the sun is out the pump pumps, when it is not, the pump stops. A thermal disconnect switch (64), is placed on the top of the hot water tank, so if it gets too hot, it will disconnect the pump.

Deleted: There is no

Deleted: 18

The invention also consists of a pressurized radiator, a pressure relief and vacuum recovery valve and fluid overflow recovery system (Fig 2). This system includes a pressurized fluid radiator (8) with fins (9) and reservoir (12), a pressure cap (10) to regulate the pressure in the system, and allow the overflowed fluid to return on system cool down at night via the relief valve in (10), which is connected to a fluid overflow and recovery reservoir (12) via tube (72) while excluding air, since the tube (72) enters the fluid (13) below the surface level. The pressure of the fluid in the solar collector heat transfer loop is regulated by the pressure cap, which uses a spring (15) to push against the fluid pressure over a fixed area. During normal daily operation when the sun is out, the heat transfer fluid (13) expands as it heats from 75 degrees Fahrenheit to over 230 degrees Fahrenheit and when the pressure reaches the set pressure, i.e. 16 PSIG, fluid and trapped air overflows to the fluid overflow reservoir (12) via tube (72), where fluid is trapped and air bubbles move to the liquid surface, burst and are vented to the atmosphere by a cap (70). At night, when the fluid in the solar heat transfer system cools and contracts, fluid only is drawn back by the vacuum created through vacuum relief valve (18), set by spring (15), into the heat transfer system to keep it full of fluid and keep air out. Air in the system can cause corrosion in the fluid loop. This simple system allows

Deleted: .

Deleted: and

Deleted: 3

Deleted: .

Deleted: .

Deleted: 2

Deleted: .

Deleted: 4

Deleted: 21

Deleted: which

Deleted: is

Deleted: 30

Deleted: .

Deleted: f

Deleted: increases the

Deleted: of

the nominal 50/50 water/antifreeze mixture in the solar heat transfer loop to heat up to over 212 degrees Fahrenheit, without boiling until it reaches almost 265 degrees Fahrenheit, at 16 PSIG confinement pressure. This high temperature allows for heat to be transferred more efficiently into the hot water tank, using lower flow rates and an internal (or external) hot water tank heat exchanger.

Deleted: approximately

Deleted: % water

Deleted:

Deleted: %

The invention also consists of a pressure activated solar collector over-temperature protection system (Fig 3). An integral part of the solar collector is a set of dampers (86 & 88) on both the top and bottom of the solar collector, which are opened by pressure actuator (6). These dampers are only open when the solar heat collected is more than the hot water tank can use and the solar collector begins to boil. These dampers when opened allow outside air of less than 120 degrees Fahrenheit to flow over the solar absorber plate (Fig1. (3)), where the sunlight is converted to heat and transferred into the heat transfer fluid. This airflow cools the absorber and stops the boiling. Then the dampers close and the absorber heats back up. The dampers open and close on a 2 to 5 minute cycle and only minor boiling is allowed to take place. This self-controlling feature is unique and allows the solar collector to be protected even if the fluid flow in the pressurized fluid loop (Fig 1. (1, 14 & 17)) stops. The dampers (vents) can be used together with the boiling activated pressurized radiator over-temperature system as shown in Fig 4.

The pressure activated control system is needed if fluid circulation stops for any reason while the sun is shining, i.e. controller turns pump off, pump failure, fluid loop blockage. The pressure activation system consists of a solar system fluid pressure-activated actuator (6), such as a piston (84), or other pressure-activated actuator, which is in a retracted state at normal system operating pressure and in an extended state at the pressure cap relief setting, such as 16 PSIG. A spring (82) or pressurized cavity can be used to return the actuator to the retracted state, when the solar system pressure falls to atmospheric pressure. The solar system fluid (13) is sealed into the system via a bellows (80) or other

Deleted: This

Deleted: 16

Deleted: 22

Deleted: atmospheric

Deleted: 20

Deleted: 21

Deleted: 23

acceptable seal, such as an O-ring. The actuator is connected to the fluid loop (7). This actuator output (5) is connected to a hinged or sliding valve (86 or 88) via a linkage (4), which allows air to flow over the solar collector absorber plate (Fig 1. (3)), cooling it with outside air. Over-temperature protection is achieved by successive airflow movements over the solar collector absorber plate. When the solar collector gets too hot the heat transfer fluid (13) boils in the solar collector. This causes the pressure actuator to extend and open the solar collector air damper valves, which take the heat out of the solar collector and the heat transfer fluid. This action drops the solar collector temperature below the boiling point and stops boiling. The system pressure returns to the set pressure and the actuator retracts and closes the solar collector air damper valves. This vent open/close cycle repeats itself until the sun goes down or the fluid flow resumes.

Deleted: 17...¶

¶
24...25...26..., like a furnace damper, and ...off
ev...ents...21...collector...to ...collector air damper valves, which take the heat out of the solar collector and the heat...atmospheric ...collector... is...reestablished... Thus the collector prevents damage to the system, by keeping the collector near the boiling point of the water/antifreeze mixture, if the hot water tank is hot enough, the pump fails to circulate the heat transfer fluid, or the fluid flow path is bloc... [1]

Figure 5 shows that the actuator and air valve position as a function of system pressure. The air valves are shut and the actuator retracted until a pressure of approximately 80% (102) of the maximum system pressure maintained by the pressure cap (Fig.4 (10)) is reached. At pressures above (102) the air valves begin to open and fully open when the system reaches 95% (104) of the system pressure (104) maintained by pressure cap (Fig.4 (10)). This arrangement allows the system to cool itself before vigorous boiling occurs. The pressure vs. actuator position profile is determined by the piston area (Fig 3. (84)) and spring (Fig 3. (82)) constant.

Deleted:

Deleted: The inset in ...3
...T...ir...are ...the actuator extended by the time..."the radiator..."22... [2]

Figure 4 shows a boiling activated radiator solar collector over-temperature protection system. The system consists of a pressurized liquid to air radiator heat exchanger and a boiling gas separator. During normal operation the entire system is full of heat transfer fluid (13) and no boiling occurs. The liquid to air heat exchanger (8) with fins (9) is a side arm and normally has no fluid flow in it. Normally the fluid flows into the boiling gas separator (94) from the solar collector tube (1) and out of it in tube (14) down to the hot water tank heat exchanger. Under non-flow conditions, such as circulating pump

Deleted: The invention also consists of a... (Fig 4)...y...21...29...abnorm... [3]

failure or the solar input being greater than the hot water tank can use, the solar collector will begin to boil. In this event the boiling gas separator (94) allows the gas bubbles (steam) to go into the liquid to air heat exchanger (8), which stirs the liquid in the heat exchanger, while condensing the boiling gas. This heat in chamber (8) is conducted to the fins (9), which heats them above outside air temperature removing heat from the fluid in radiator (8). The filler tube (92) allows liquid to come from the liquid to air radiator (8) and be inserted below where the gas bubbles are being released, tube (1) in the boiling gas separator (94), keeping the collector fluid loop (1, 14 & 17) full of liquid. The system allows a small amount of boiling to take place, which rejects heat to the atmosphere via the pressurized liquid to air radiator, heat exchanger. As long as boiling takes place the liquid in the radiator (8) will be heated by condensing the boiling gas. Only a small amount of fluid (13) will be forced through tube (72) into the fluid overflow reservoir (12) on cooling vacuum will draw only fluid (13) from reservoir (12) back into the system. The advantage of this system is that it has no moving parts and can be made to dissipate all of the heat that the solar collector gathers from the sun.

Deleted: 28

Deleted: 29

Deleted: and

Deleted: heats it

Deleted: and dissipates this heat to the outside air

Deleted: 27

Deleted: exchanger

Deleted: 28

Deleted: 1

Deleted: , which

Deleted: their

Deleted: side arm heat exchanger

Deleted: a

Deleted: a

Deleted: steam

Deleted: condenser (4)

Deleted: easily

Deleted: can

ABSTRACT

Delivering heat from modern high temperature solar collectors to a hot water storage tank's internal heat exchanger is more effectively done using a fluid filled, thermal expansion pressurized, fluid heat transfer loop, using a water based antifreeze, a pressurized radiator, a pressure cap/vacuum relief and overflow reservoir. Fluid at 16 psi boils at 265°F. The fluid filled pressurized loop automatically eliminates trapped air using a pressurizing/vacuum recover cap and overflow reservoir with gas and liquid entering below the waterline so only liquid can return to the loop. The system protects itself from loss of fluid circulation by boiling under pressure. The steam produced by the solar collector is either condensed in the pressurized liquid to air radiator giving up its heat to the outside air, or the steam pressure will be used to open dampers on the solar collector allowing air to pass over and cool the solar collector.

Deleted: s

Deleted: , high temperature

Deleted: non-flammable and low toxicity

Deleted: heat transfer fluids

Deleted: and is the subject of this patent. Non-toxic water/antifreeze mixtures can be used in pressurized (14#, (14 Pounds Square Inch pressure above atmosphere)) systems

Deleted: up

Deleted: to

Deleted:

Formatted: Superscript

Deleted: degrees Fahrenheit before the mixture boils

Deleted:

Deleted: Boiling

Deleted: transports either steam or heat out of the closed system.

Deleted: must be

Deleted: and returned to the closed loop system to keep it full. In order to accomplish this in a practical manner a pressurizing cap and overflow reservoir are used.

Deleted: The

Deleted: system will either shed excess heat collected by boiling or limit the heat input from the collector panel by increasing its heat loss due to increasing solar collector temperature above ambient.

Claims

1. (currently amended): A self pressurized by fluid thermal expansion or phase change (water to steam) fluid filled closed loop solar collection system for delivering solar energy from a roof mounted collector panel to a hot water tank including: a pressurization system capable of maintaining system pressures above atmospheric pressure to increase the boiling point of the heat transfer fluid; a pressurized fluid radiator/overflow/recovery apparatus to catch overflow heat transfer fluid and trapped air and return the fluid to the system by vacuum while keeping air out; a heat transfer fluid to air pressurized radiator and or solar collector pressure activated air dampers to prevent the solar collectors from overheating during no flow conditions; a water based antifreeze heat transfer fluid to prevent damage from freezing in winter environments; a means to connect solar collector and water tank heat exchanger together; a circulation pump; control system and an internal heat exchanger which is adaptable to the hot water tank, to deliver heat from the heat transfer fluid to the hot water tank.

Deleted: collector

Deleted: domestic

Formatted: Font: 12 pt

Formatted: Font: 12 pt

Deleted: nts

Formatted: Font: 12 pt

Formatted: Font: 12 pt

Deleted: ve

Formatted: Font: 12 pt

Deleted: an

Formatted: Font: 12 pt

Deleted: flexible umbilical

Deleted: double walled

Deleted: existing

Formatted: Font: 12 pt

Formatted: Font: 12 pt

Formatted: Font: 12 pt

Formatted: Font: 12 pt

Formatted: Font: 12 pt

Deleted: to

Deleted: reach a

Deleted: and allows condensed water

Deleted: returned to

Deleted: fluid loop.

2. (currently amended): A boiling activated pressurized radiator solar collector over-temperature protection system which includes a pressurized fluid to air radiator/overflow/recovery apparatus to catch overflow heat transfer fluid and trapped air and return the fluid to the system using vacuum while keeping air out, utilizes no moving actuators, and includes a boiling gas/liquid separator, which allows steam condensed in the pressurized liquid to air radiator to be kept in the pressurized fluid loop so the sun's heat energy is dissipated to the ambient air flowing over the pressurized radiator and when the collector boiling stops, the sun's heat energy is delivered to the circulating heat transfer fluid and then to the hot water tank.

3. (currently amended): A pressure activated solar collector over-temperature protection system which utilizes solar collector air dampers as moving parts, including: a steam

pressure activated mechanical actuator, which opens before the systems' regulated pressure is reached; and a set of damper valves, which control airflow over the solar collector panel, so when opened the sun's heat energy is dissipated to the flowing ambient air and then when the dampers are closed the sun's heat energy is delivered to the circulating heat transfer fluid and thus to the hot water tank.

Deleted: loop

4. (cancelled): ,

Deleted: currently amended

5. (currently amended): The system as in claim 1 or claim 2 comprised of a 220/115 VAC controller and pump and boiling activated over-temperature protection,

Deleted: A flexible umbilical assembly that carries and insulates the heat transfer fluid tubing while protecting it from the elements with a clamp-on "clam-shell" split pipe external covering and includes all electrical connections between the solar collector and the hot water tank.

6. (currently amended): The system as in claim 1 or claim 3 comprised of a 220/115 VAC controller and pump, with pressure activated over-temperature protection,

Deleted: currently amended

Deleted: according to

Deleted: ,

Deleted: with a

Deleted: according to claim 2

Deleted: currently amended

7. (currently amended): The system as in claim 1 or claim 2 comprised of a a photovoltaic panel and low voltage (12VDC) pump, with boiling activated over-temperature protection,

Deleted: The system according to claim 1, with a

Deleted: according to claim 3.

Deleted: currently amended

Deleted: Th

8. (currently amended): The system as in claim 1 or claim 3 comprised of a a photovoltaic panel and low voltage (12VDC) pump, with pressure activated over-temperature protection,

Deleted: e system according to claim 1, with

Deleted: according to claim 2

Deleted: currently amended

Deleted: The system according to claim 1, with a

Deleted: according to claim 3